§MAVERICK™ X3 X™ ds TURBO RR

PLATFORM FEATURES

- 162.5 cm wide
- 259 cm wheelbase
- 35.6 cm of ground clearance
- High torque Dynamic Power Steering (DPS[™])
- 51 cm suspension travel

SPECIFIC TO X ds PACKAGE

- 195 hp Turbo RR engine Smart-Lok™* front differential
- FOX[†] 2.5 PODIUM[†] RC2 Piggyback shocks
- 14-in. aluminum beadlock wheels
- 29-in. Maxxis† Bighorn 2.0† tires
- X-package graphics/seats
- 7.6-in. digital display with keypad

DEFIANT

- Trademark Can-Am DNA with 195 hp turbocharged and next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

POWERFUL

- intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features





Iron gray & Manta Green / TURBO RR

ENGINE	TURBO RR
Туре	195 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
	*Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)

5 11 4 11 1 1500 1
Double A-arm with sway bar / 50.8 cm travel
5 PODIUM RC2 Piggyback with dual speed compression and rebound adjustments
4-link Torsional Trailing-arm X (TTX) with sway bar 50.8 cm travel
2.5 PODIUM RC2 Piggyback with dual speed compression, rebound adjustments and bottom-out control

BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHE	ELS
Front Tires	Maxxis Bighorn 2.0 29 x 9 x 14 in. (73.7 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 29 x 11 x 14 in. (73.7 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

DIMENSIONS /	CAPACITIES		
LxWxH	335.3 x 162.5 x 166.9 cm		
Wheelbase	259.1 cm		
Ground Clearance	35.6 cm		
Estimated Dry Weight	680.9 kg		
Chassis / Cage	Dual-phase 980 steel		
Rack Capacity	91 kg with LinQ™ quick-attach		
Storage Capacity	Total: 9.4 L Glove box: 6.2 L Center console: 2.8 L Cup holders: 0.4 L		
Fuel Capacity	40 L		

FEATURES			
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour	Protection	Integrated front bumper, quarter-doors, HMWPE full skid plate, rear tow hook
	meters, fuel, gear position, SPORT / ECO™ modes, seat belt, diagnostics, clock	Instrumentation	Lighter type DC outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY		
Factory	2 years	



