§MAVERICK™ TRAIL DPS™ 800 T

AGILE

- · Sturdy engine and transmission
- Easy Handling and capabilities
- Front and rear suspension designed for trail riding

ADVENTUROUS

- Meaningful functionalities and versatilities
- Enhanced comfort with Ergo-Lok cockpit
- Build your Maverick Trail that fits your needs

CONFIDENT

- · Can-Am design and proven fit & finish
- Enhanced protection
- More adventure and less maintenance

SPECIFIC TO DPS PACKAGE

- Dynamic Power Steering (DPS™)
- Dynamic Brake and Traction Control System
- Lockable rear differential
- SPORT / ECO™ modes
- 12-in. cast-aluminum wheels
- Ergoprint seats with color accent



Can-Am Red

ENGINES	800
Туре	55 hp, Rotax® 799.9 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with lockable rear differential
Driving assistance	Brake and Traction Control System SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
Speed category	More than 60 km/h

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar 25.4 cm travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar 26.7 cm travel
Rear Shocks	Twin tube gas charged shocks

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	Standard

TIRES / WHEI	ELS
Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12-in. (30.5 cm) cast-aluminum

DIMENSIONS /	CAPACITIES
LxWxH	300.5 x 127 x 175.5 cm
Wheelbase	230.1 cm
Ground Clearance	25.4 cm
Dry Weight	603.7 kg
Cage	ROPS-approved profiled cage. Certified ISO 3471.
Cargo Box Capacity	136 kg
Storage Capacity	Total: 20.2 L Glove Box: 15.6 L Driver storage: 1.5 L Center console and Cup holders: 3.1 L
Towing capacity	680 kg

38 L

FEATURES			
Gauge	7.6 in. (19.3 cm) wide digital display with keypad	Winch	Prewired for available winch
		Steering Wheel	Adjustable tilt steering
Instrumentation	Lighter type DC outlet in console (20-A)	Protection	Integrated front steel bumper, injected full body skid
Magneto	650W		plates, mudguards, mudflaps
Lighting	Two 55 W reflectors	Hitch Type	2-in. hitch receiver with tow ball, 7-pin trailer connection (12V)
T-category features	Horn, flashers and position lamps, mirrors, hook on front metal bumper		

WARRANTY	
Factory	2 years



Fuel Capacity



§MAVERICK™ TRAIL DPS™ 1000 T

HIGHLIGHTS

AGILE

- Sturdy engine and transmission
- Easy Handling and capabilities
- Front and rear suspension designed for trail riding

ADVENTUROUS

- Meaningful functionalities and versatilities
- Enhanced comfort with Ergo-Lok cockpit
- Build your Maverick Trail that fits your needs

CONFIDENT

- Can-Am design and proven fit & finish
- Enhanced protection
- More adventure and less maintenance

SPECIFIC TO DPS PACKAGE

- Dynamic Power Steering (DPS™)
- Dynamic Brake and Traction Control System
- Lockable rear differential
- SPORT / ECO[™] modes
- 12-in. cast-aluminum wheels
- Ergoprint seats with color accent



Can-Am Red

Fuel Capacity

ENGINES	1000
Туре	75 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System(QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with lockable rear differential
Driving assistance	Brake and Traction Control System SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
Speed category	More than 60 km/h

SUSPENSIONS		
Front Suspension	Double A-arm with sway bar 25.4 cm travel	
Front Shocks	Twin tube gas charged shocks	
Rear Suspension	TTA with sway bar 26.7 cm travel	
Rear Shocks	Twin tube gas charged shocks	

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	Standard

TIRES / WHEELS	
Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS /	CAPACITIES
LxWxH	300.5 x 127 x 175.5 cm
Wheelbase	230.1 cm
Ground Clearance	25.4 cm
Dry Weight	618.7 kg
Cage	ROPS-approved profiled cage. Certified ISO 3471.
Cargo Box Capacity	136 kg
Storage Capacity	Total: 20.2 L Glove Box: 15.6 L Driver storage: 1.5 L Center console and Cup holders: 3.1 L
Towing Capacity	680 kg

38 L

FEATURES					
Gauge	7.6 in. (19.3 cm) wide digital display with keypad	Winch	Prewired for available winch		
		Steering Wheel	Adjustable tilt steering		
Instrumentation	Lighter type DC outlet in console (20-A)	Protection	Integrated front steel bumper, injected full body s		
Magneto	650W		plates, mudguards, mudflaps		
Lighting	Two 55 W reflectors	Hitch Type	2-in. hitch receiver with tow ball, 7-pin trailer connection (12V)		
T-category features	Horn, flashers and position lamps, mirrors, hook on front metal bumper				

W				

Factory 2 years





