## **©OUTLANDER™ PRO 450**

- Rotax® engine
- Intelligent Throttle Control (iTC™)
- Continuously Variable Transmission (CVT)
- Tri-Mode Dynamic Power Steering (DPS)
- 26-in. 6-ply Carlisle† ACT HD radial tires
- Double A-arm front suspension
- Visco-Lok QE auto-locking front differential
- 590 kg towing capacity
- RF Digitally Encoded Security System (D.E.S.S.)
- Multifunction digital gauge

- Steel racks with LinQ quick-attach accessory system and a combined 163.3 kg capacity
- 10.9 L water-resistant rear compartment
- · Reinforced seat skin
- Increased ground clearance
- Relocated air intakes



Green

ENGINES	450
Туре	38 hp, Rotax 427 cc single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

Туре	38 hp, Rotax 427 cc single cylinder, liquid cooled		Carlisle <sup>†</sup> ACT HD 26 x 8 x 12-in.
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		(66 x 20.3 x 30.5 cm)
Transmission	CVT, P / R / N / H / L, standard engine braking	Rear Tires	Carlisle <sup>†</sup> ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential	Wheels	12-in steel
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		22 0.001

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	0il
Rear Suspension	Torsional Trailing arm Independent (TTI) 22.4 cm travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

DIMENSIONS / CA	PACITIES
LxWxH	211 x 117 x 124 cm
Wheelbase	129.5 cm
Ground Clearance	29.2 cm
Seat Height	85.8 cm
Dry Weight*	308 kg
Rack Capacity	Front: 54.4 kg Rear: 109 kg
Storage Capacity	Rear: 10.9 L
Towing Capacity	590 kg
Fuel Capacity	20.5 L

<b>FEATURES</b>			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip &	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70-W from dual 35-W front light / brake light
		Seat	Reinforced seat skin
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

WARRANTY	
Factory	2 years



## **SOUTLANDER** PRO 570

## HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC<sup>™</sup>) with riding modes
- Continuously Variable Transmission (CVT) with Extra Low L-gear
- Tri-Mode Dynamic Power Steering (DPS)
- 26-in. 6-ply Carlisle<sup>†</sup> ACT HD radial tires
- Double A-arm front suspension
- Visco-Lok QE auto-locking front differential
- 590 kg towing capacity
- RF Digitally Encoded Security System (D.E.S.S.)
- Multifunction digital gauge

- Steel racks with LinQ quick-attach accessory system and a combined 163.3 kg capacity
- 10.9 L water-resistant rear compartment
- Reinforced seat skin
- Increased ground clearance
- Relocated air intakes



Green

ENGINES	570
Туре	48 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC <sup>TM</sup> ) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

TIRES / WHEELS	
Front Tires	Carlisle <sup>†</sup> ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle <sup>†</sup> ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. steel

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 22.4 cm travel
Rear Shocks	Oil

<b>DIMENSIONS / CA</b>	APACITIES
LxWxH	211 x 117 x 124 cm
Wheelbase	129.5 cm
Ground Clearance	29.2 cm
Seat Height	85.8 cm
Dry Weight*	319 kg
Rack Capacity	Front: 54.4 kg Rear: 109 kg
Storage Capacity	Rear: 10.9 L
Towing Capacity	590 kg
Fuel Capacity	20.5 L

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

<b>FEATURES</b>			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip &	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70-W from dual 35-W front light / brake light
		Seat	Reinforced seat skin
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

WARRANTY	
Factory	2 years

